

## **ISOcofcoated.icc**

Das ECI-Offsetprofil **ISOcofcoated.icc** basiert auf der Endlosdruck Charakterisierungsdatei „**FOGRA31L.txt**“ und gilt für die folgenden Druckbedingungen gemäß internationalem Standard ISO/DIS 12647-2:2003+:

Offset, Endlosdruck, Papiertyp 2, matt gestrichen Bilderdruck, 115 g/m<sup>2</sup>, Positivkopie, **Rasterweite 60/cm (150 lpi), weiße Messunterlage (wb).**

Die Profilberechnung erfolgte in Heidelberg Printopen 4.0.5.2 mit den folgenden Einstellungen:

Schwarz-Länge	9
Schwarz-Breite	5
max. Flächendeckung	350%
max. Schwarz	100 %

Die „Gamut-Mapping“-Option „mehr Kontrast in dunklen Farben“ war ausgeschaltet.

---

*The ECI offset profile **ISOcofcoated.icc** is based on the offset characterization table “**FOGRA31L.txt**” valid for the following reference printing conditions relating to the international standard ISO/DIS 12647-2:2003+:*

*Continuous forms printing, paper type 2, matt coated paper, 115 g/m<sup>2</sup>, positive plates, **screen frequency 60/cm (150 lpi), white backing (wb).***

*The profile was generated using Heidelberg Printopen 4.0.5.2 with the following settings:*

<i>Black length</i>	<i>9</i>
<i>Black width</i>	<i>5</i>
<i>Total dot area</i>	<i>350%</i>
<i>Maximum Black</i>	<i>100 %</i>

*The “Gamut-Mapping” option “More contrast in dark colors” was switched off.*